

Vaisala CARBOCAP® Carbon Dioxide Probe GMP343

		Fill here										0	PRICE
<b>Vaisala CARBOCAP® Carbon Dioxide Probe GMP343</b>													
Sampling method	<b>diffusion</b>	A											
	<b>flow through</b>	B											
Measurement range of the probe:	<b>0...1000 ppm CO<sub>2</sub></b>	1											
	<i>0...2000 ppm CO<sub>2</sub></i>	2											
	<i>0...3000 ppm CO<sub>2</sub></i>	3											
	<i>0...4000 ppm CO<sub>2</sub></i>	4											
	<i>0...5000 ppm CO<sub>2</sub> *</i>	5											
Analog output selection **	<b>0...5V</b>	A											
	<b>0...2.5 V</b>	B											
	<b>4...20 mA</b>	C											
Digital output selection	<b>RS-232</b>	1											
	<b>RS-485 ***</b>	2											
Probe cable	<b>none</b>	N											
	<i>probe cable (with M12 type female connector), 2 m</i>	A											
	<i>probe cable (with M12 type female connector), 6 m</i>	B											
	<i>probe cable (with M12 type female connector), 10 m</i>	C											
Measurement indicator MI70 and accessories	<b>none</b>	0											
	<i>MI70 indicator and interface cable, 2 m****</i>	1											
	<i>MI70 interface cable, 2 m</i>	2											
Calibration accessories	<b>none</b>	N											
	<i>calibration adapter for diffusion model.</i>	A											
	<i>PC connection cable</i>	B											
	<i>calibration adapter for diffusion model and PC connection cable</i>	C											
Mounting accessories	<b>none</b>	0											
	<i>mounting flange</i>	1											
Wiring accessories	<b>none</b>	N											
	<i>junction box</i>	A											
Reserved for future use		0											
Manual	<b>no manual</b>	A											
	<b>English</b>	B											
												TOTAL	
												QTY	
												TOTAL VALUE	

Selections in bold are included in the prices of the basic versions.

Selections in italic are available at an extra price.

Shaded sections indicate typical selections.

**Notes:**

\* The range 0...5000 ppm CO<sub>2</sub> has reduced accuracy specifications above 4000 ppm CO<sub>2</sub>.

\*\* The selected analog output may be re-scaled using PC connection cable, while the voltage/current selection change-over may not.

\*\*\* If the selection is RS-485, the device may be powered up in the RS-232 service mode for user settings. See user manual for details.

\*\*\*\*This selection includes:

- MI70 indicator with a rechargeable battery
- AC adapter with AUS, EUR, UK and US plugs
- MI70Link software with RS232 cable (PC<->MI70)
- 2 m interface cable (GMP343 <-> MI70)

Example of order code:

**GMP343 A 1 A 1 A O A O N 0 B**

**Accessories and Spare Parts:**

Included in the default configuration

Included in the default configuration of the diffusion model

**Description**

- Wall mount bracket
- Mounting flange
- Weather protection + diffusion filter
- Calibration adapter
- Junction box
- Probe cable (with M12 type female conn.), 2 m
- Probe cable (with M12 type female conn.), 6 m
- Probe cable (with M12 type female conn.), 10 m
- PC connection cable
- Interface cable for MI70, 2 m

**Order Code**

- GMP343BRACKET
- GMP343FLANGE
- GMP343FILTER
- GMP343ADAPTER
- JUNCTIONBOX-8
- GMP343Z200SP
- GMP343Z600SP
- GMP343Z1000SP
- 213379
- DRW216050SP

**PRICE**