

BECO filter cartridges for
chemistry, cosmetics and
biotechnology applications



Powering Business Worldwide

Wide range of filter cartridges offer complete filtration solutions for chemistry, cosmetics and biotechnology applications

Eaton provides high-quality wrapped and pleated depth filter and membrane filter cartridges.

The BECO® filter cartridge selection offers a wide range of solutions from clarifying and fine filtration with depth filter cartridges (BECO PROTECT®) to the reduction and retention of microorganisms with membrane filter cartridges (BECO MEMBRAN).

To efficiently protect downstream membranes and extend their service life, Eaton can recommend the optimal combination of pre-filter and membrane filter cartridges.

BECO filter cartridges feature a variety of retention ratings, between 0.2 and 150 µm, suitable for an array of liquid filtration applications. In addition to sizes ranging from 10" (25 cm) to 40" (100 cm) and also various adapter codes, filter cartridges are available with different filter material. All BECO MEMBRAN filter cartridges are testable for integrity and therefore offer high process reliability for the user.

The product range contains numerous housings and system solutions for the use of depth filter and membrane filter cartridges, such as the BECO INTEGRA® CART stainless steel filter cartridge housings and complex, automatic StepFlow® filtration systems.

Eaton filter cartridges meet national and international quality standards, such as the LFGB standard (German Food, Commodity and Feed Act) in Germany and FDA guidelines (Food and Drug Administration) from the USA. The plastic components meet European Directive (EU) 10/2011.



BECO Filter Cartridges

Selection guide

DEPTH FILTER CARTRIDGES



BECO PROTECT PG

Consist of up to 24 wrapped polypropylene fleeces that are graded from coarse to fine. The funnel design ensures that a wide particle spectrum can be absorbed, with a high retention rating and excellent backwashing capability.



BECO PROTECT FS FineStream

Provide optimal protection of downstream membrane filter cartridges through special pleated polypropylene fleece. The innovative and unique special pleating increases the filter area and achieves unparalleled efficiency of retention. The variable flow rate is also unique.



BECO PROTECT PP Pure

Consist of pleated polypropylene filter material, featuring a high efficiency of retention and a large filter area for high flow rates.

MEMBRANE FILTER CARTRIDGES



BECO MEMBRAN PS Aqua

Special polyethersulfone membrane filter cartridges with a retention rate of 0.2 µm and high flow rates and long service life for the filtration of water.



BECO MEMBRAN PSplus

Excellent pleated membrane filter cartridges for sterile filtration constructed from special asymmetrical polyethersulfone (PES) material. They are testable for integrity and guarantee an excellent microbial retention and a long service life thanks to the excellent mechanical and thermal stability. With a wide range of retention rates from 0.2 to 1.0 µm, these filter cartridges generally meet all requirements for the final filtration of in chemical, cosmetics and biotechnology industries.

FILTER CARTRIDGES FOR SERVICE MEDIA



BECO PROTECT PB

Depth filter cartridges constructed of thermally bonded, melt-blown polypropylene filter material with high dirt-holding capacity and high chemical resistance. No inner core or outer cage is required due to the mechanical stability of the filter cartridges.



BECO PROTECT HF HighFlow

Depth filter cartridges made of pleated, multi-layer and thermally bonded polypropylene filter material, which offers a large surface area, maximum efficiency and exceptionally high flow rates.



BECO PROTECT CL Coreless

Depth filter cartridges made of wrapped polypropylene filter material with different layers from coarse to fine. The filter cartridges are manufactured without a core and with a large diameter to provide high flow rates.



BECO PROTECT KM

Stainless steel filter cartridges that are constructed from porous metal powder (316L) predominately used in steam filtration for the separation of rust particles and abraded matter. These cartridges are designed for liquid filtration at high temperatures.



BECO MEMBRAN H Air and H Air Mini

Membrane filter cartridges that retain contaminants up to 0.01 µm and are primarily used for sterile filtration of gases and air. Available in 1", 5", 10", 20" and 30".

ADAPTER CODES



Code X: Double open end (DOE) without end caps



Code F: Double open end (DOE) with two flat gaskets



Code 0: Single open end (SOE), 2-222 O-ring without spear, external diameter 44 mm (bottom-most point)



Code 2: Single open end (SOE), 2-222 O-ring, triple bayonet-adapter with spear, external diameter 44 mm (bottom-most point)



Code 7: Single open end (SOE), 2-226 O-ring, double bayonet-adapter with spear, external diameter 56 mm (bottom-most point)

Technical data

	BECO PROTECT PG	BECO PROTECT FS	BECO PROTECT PP Pure	BECO PROTECT PB	BECO PROTECT HF	BECO PROTECT CL	BECO PROTECT KM
Article number	PG002–PG995	FS002–FS200	PPP6–PPP10	PB005–PB250	HF010–HF100	CL050–CL400	KM10
Filter material	Polypropylene (PP)	Polypropylene (PP)	Polypropylene (PP)	Polypropylene (PP)	Polypropylene (PP)	Polypropylene (PP)	Stainless steel 316L (1.4404)
Retention rating (µm)	0.2, 0.3, 0.5, 0.6, 0.8, 1, 2, 3, 5, 10, 15, 20, 30, 40, 50, 75, 100, 120, 150	0.2, 0.3, 0.5, 0.6, 0.8, 1, 2, 3, 5, 10, 20	0.6, 1.2, 3, 5, 10	0.5, 1, 5, 10, 25	1, 3, 5, 10	5, 10, 20, 40	10
Retention efficiency	99.98%	99.98%	99.98%	90%	99.98%	99.98%	Nominal
Lengths	9.75", 10", 19.5", 20", 29.5", 30", 40"	10", 20", 30", 40"	10", 20", 30", 40"	9.75", 10", 19.5", 20", 29.5", 30", 39", 40"	40"	40"	10", 20", 30"
Adapter codes	X, F, 0, 2, 7	F, 0, 2, 7	0, 2, 7	X, F	U**	X	7
Cages	Yes	Yes	Yes	No	Yes	No	No
Backwashability	Up to 2.0 bar at 80°C	Up to 2.0 bar at 80°C	Up to 2.0 bar at 80°C	Yes	–	–	Up to 1.0 bar at 25°C
Chemical resistance	pH 1–14	pH 1–14	pH 1–14	pH 1–14	–	–	pH 1–14
Max. operating temperature	80°C	80°C	80°C	65°C	80°C	80°C	200°C
Max. differential pressure in flow direction	4.8 bar at 25°C 2.0 bar at 80°C	4.8 bar at 25°C 2.0 bar at 80°C	5.0 bar at 20°C 2.0 bar at 80°C	3.2 bar at 20°C 1.2 bar at 60°C	3.4 bar at 20°C	4.0 bar at 30°C 1.0 bar at 80°C	–
Steam cycles	> 100 at 110°C in 30 minutes	> 100 at 110°C in 30 minutes	> 100 at 110°C in 30 minutes	Not recommended	Max. 10 at 121°C in 15 minutes	–	–

	BECO MEMBRAN PS Aqua	BECO MEMBRAN PSplus	BECO MEMBRAN H Air	BECO MEMBRAN H Air Mini
Article number	PSA02	PES02, PES04, PES06, PES10	PTC02	PTM02
Filter material	Polyethersulfone (PES)	Polyethersulfone (PES)	Polytetrafluorethylene (PTFE)	Polytetrafluorethylene (PTFE)
Retention rating (µm)	0.2	0.2, 0.45, 0.65, 1.0	0.2	0.2
LRV (Titer reduction/cm²)*	> 7	> 7 1 µm: 6	> 7	> 7
Lengths	30"	10", 20", 30", 40"	10", 20", 30"	1", 5"
Adapter codes	2, 7	0, 2, 7	7	1, 4, 7
Cages	Yes	Yes	Yes	Yes
Pressure hold test Test pressure in bar and diffusion rate per 10'	PSA02 2.5 bar ≤ 20 ml/min	PES02 2.4 bar ≤ 20 ml/min PES04 1.7 bar ≤ 20 ml/min PES06 1.0 bar ≤ 20 ml/min PES10 0.6 bar ≤ 20 ml/min	PTC02 Nitrogen diffusion at 20°C per 10' ≤ 7 ml/min at 0.7 bar with 60% isopropanol	PTM02 Bubble point test at 23°C ≥ 1000 mbar in 60% isopropanol
Chemical resistance	pH 1–14	pH 1–14	pH 1–14	pH 1–14
Max. operating temperature	80°C	80°C	80°C	80°C
Max. differential pressure in flow direction	5.0 bar at 20°C 0.3 bar at 121°C	5.0 bar at 25°C 0.3 bar at 121°C	5.0 bar at 20°C 0.5 bar at 134°C	5.0 bar at 20°C 0.5 bar at 134°C
Steam cycles	≥ 100 at 105°C in 30 minutes	≥ 100 at 110°C in 30 minutes	≥ 150 at 134°C in 20 minutes	50 at 134°C in 20 minutes

* Please see technical data sheets for further information about the used test organisms ** Code U (SOE) for BECO PROTECT HF HighFlow filter cartridges only



Segments and Applications

Biotechnology

Coarse and fine filtration, particle removal, polishing filtration, catalyst recovery, water and process liquid filtration, filtration of buffer and solvents, chromatography prefiltration, sterile process filtration.

Fine chemical / API

Coarse and fine filtration for organic and inorganic compounds, catalyst removal, clarifying filtration, amine filtration, silicone oil filtration, RO and UF prefiltration. Prefiltration and final filtration of acids and bases, organic and inorganic solvents, buffer solutions, filtration of feed water, activated carbon removal, sterile filtration, sterile gas filtration and tank venting.

Cosmetic, flavour and fragrances

Clarifying and fine filtration, water and process liquid filtration, solvent filtration, winterizing, germ removal, sterile air and gas filtration.

Paint and resins

Particle removal, selective filtration, solvent filtration, colloid filtration, salt removal and haze reduction, particle filtration.

Oils and fats

Particle removal, polishing, haze reduction and tank venting.

		Filter Cartridges									Filter Cartridge Housings				
		BECO PROTECT						BECO MEMBRAN			For Liquid		For Air, Steam & Gas		
		PG	FS	PP Pure	PB	HF	CL	KM	PS Aqua	PSplus	H Air/ H Air Mini	KA	KHF/ KCL	KK	KLAV
Segment	Biotechnology	■	■	■					■	■	■	■		■	■
	Fine chemical / API	■	■	■					■	■	■	■		■	■
	Cosmetic	■	■	■	■				■	■		■			
	Flavour and fragrances	■	■	■	■					■		■			
	Paint and resins	■	■		■			■	■			■			
	Oils and fats				■										
Application	Coarse filtration	■	■		■	■	■					■	■		
	Fine filtration	■	■	■								■			
	Sterile filtration								■	■	■	■			
	Solvent filtration	(■)	(■)	(■)	(■)			■	(■)	(■)	■	■			
	Water treatment (Utilities)	■	■		■	■	■						■		
	Water filtration (Process)	■	■	■		■	■		■	■			■		
	Activated carbon retention	■	■									■			
	Upstream bioreactor	■	■	■				■	■	■	■	■		■	■
	Final filtration	■	■	■					■	■	■	■		■	■
	Buffer filtration								■	■		■			
	Steam filtration							■						■	■
	Air and gas filtration	■		■				■			■			■	■
	Tank venting filtration										■			■	■

(■) : Limited use, depending on the used solvent

FILTER CARTRIDGE HOUSINGS



BECO INTEGRA CART KA

These filter cartridge housings are manufactured from AISI 316L stainless steel and can be used for the liquid filtration in chemistry, cosmetics and biotechnology industries. They are available in 1-, 3-, 5-, 8-, 12-, 18-, 24- and 30-fold cartridge versions for pre-filtration or sterile filtration purposes.



BECO INTEGRA CART KHF/KCL

Are manufactured of stainless steel AISI 316L and can be applied for the filtration of liquids with high flow rates in Life Science applications. This series is available as a 1 x 40" version.



BECO INTEGRA CART KK

These filter cartridge housings are manufactured from AISI 316L stainless steel and designed for pressurized air or steam filtration applications.



BECO INTEGRA CART KLAV

These filter cartridge housings are manufactured from AISI 316L stainless steel and are used as vent filter housings for gas filtration. This series is suitable for sterile filtration for filter cartridges with a code 1 adapter.

North America
44 Apple Street
Tinton Falls, NJ 07724
Toll Free: 800 656-3344
(North America only)
Tel: +1 732 212-4700

Europe/Africa/Middle East
Auf der Heide 2
53947 Nettersheim, Germany
Tel: +49 2486 809-0
Friedensstraße 41
68804 Altlußheim, Germany
Tel: +49 6205 2094-0

An den Nahewiesen 24
55450 Langenlonsheim, Germany
Tel: +49 6704 204-0

Greater China
No. 7, Lane 280,
Linhong Road
Changning District, 200335
Shanghai, P.R. China
Tel: +86 21 2899-3687

Asia-Pacific
100G Pasir Panjang Road
#07-08 Interlocal Centre
Singapore 118523
Tel: +65 6825-1620

**For more information, please
email us at filtration@eaton.com
or visit www.eaton.com/filtration**

© 2023 Eaton. All rights reserved. All trademarks and registered trademarks are the property of their respective owners. All information and recommendations appearing in this brochure concerning the use of products described herein are based on tests believed to be reliable. However, it is the user's responsibility to determine the suitability for his own use of such products. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Eaton as to the effects of such use or the results to be obtained. Eaton assumes no liability arising out of the use by others of such products. Nor is the information herein to be construed as absolutely complete, since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations.

EN
1 A 4.5.1
04-2023