

# EF and FHS Series Flexible Fixture Hangers

## Hook and Loop

UNILETS® for Use with Threaded Rigid Metal Conduit and IMC.

CEC:  
Listed for Ordinary (Unclassified) Locations

### Applications

- Designed for suspension of HID, fluorescent and incandescent lighting fixtures.

### Features

- Protect fixture against wind and vibration damage.
- Cushion type for added protection where lighting fixtures are subjected to vibration.
- EF hook and loop hangers
  - Malleable iron for strength and safety.
  - Hook and loop combination permits quick disconnect and removal of fixture for maintenance.
  - Offer inexpensive means of pendant flexible suspension of lighting fixtures.
  - Permit free swing in any direction.
  - EF jaw openings can be completely closed for added safety.
- FHS support hangers
  - Provide up to 158.8 kg (350 lbs) support for fluorescent fixtures on the non-electrical side of mounting.
  - Straddle a maximum of 1-1/4" conduit and take 1/2" or 3/4" fixture hook or conduit.

### Standard Materials

- Malleable iron



EFHM



EFHF



FHS

### Standard Finishes

- Zinc electroplate and clear chromate

### CEC Certifications and Compliances

- CSA Certified: 065180

POLES/HANGERS: NEC/CEC ORDINARY LOCATION FLEXIBLE FIXTURE HANGERS

	Size (Inches)	Length A mm (in)	Support Weight kg (lbs)	Catalog Number
--	---------------	------------------	-------------------------	----------------

#### EF – Safety Support Hooks – With 3/8" jaw opening



EFHM



EFHF

#### EFHM – Male

1/2

66.8 (2.63)

90.0 (200)

EFHM-50

3/4

74.7 (2.94)

EFHM-75

#### EFHF – Female

1/2

50.8 (2.00)

90.0 (200)

EFHF-50

3/4

52.1 (2.05)

EFHF-75

#### FHS – Support for Fixtures, Dummy Side – Straddles up to 1-1/4" trade size conduit – 11/32" diameter mounting holes, spaced 3-1/4" apart



1/2 or 3/4

87.1 (3.31)

157.5 (350)

FHS5075

#### Dimensions in Millimeters (Inches)

	A	B	C	Catalog Number
<b>EFHM – Male</b>	1/2-14 NPT	50.8 (2.00)	66.8 (2.63)	EFHM-50
	3/4-14 NPT	54.1 (2.13)	73.2 (2.88)	EFHM-75
<b>EFHF – Female</b>	1/2-14 NPT	50.8 (2.00)	N/A	EFHF-50
	3/4-14 NPT	54.1 (2.13)	N/A	EFHF-75

