

**Membrane Filtration**  
**BECO® MEMBRAN PS Aqua**

**Membrane Filter Cartridges**

**BECO MEMBRAN PS Aqua filter cartridges are designed for reliable removal of spoilage microorganisms and meet extended service life requirements of water final filtration in food and beverage applications. Eaton can suggest the most economical configuration of pre and final filter.**

**Features and Benefits**

- The high filter area and asymmetric membrane structure of polyethersulfone offers exceptionally high flow rates and outstanding service life
- The special design allows for 72.5 psid (5 bar) differential pressure in the direction of flow and 29 psid (2 bar) differential pressure in reverse to support a long service life
- The high thermal stability allows for more than 100 steam sterilization cycles
- Wide broad chemical compatibility from pH 1-14

**Configuration**

BECO MEMBRAN PS Aqua filter cartridges are made of high-quality polyethersulfone membranes. Polypropylene support fleeces protect the membrane and provides wide chemical compatibility, while the polypropylene cage and core help to ensure maximum mechanical stability.



**Materials**

<b>Filter membrane:</b>	Polyethersulfone
<b>Support fleeces:</b>	Polypropylene
<b>Cage, core</b>	Polypropylene
<b>End cap/adapter:</b>	Polypropylene, adapter with reinforcing ring
<b>O-rings:</b>	Silicone (standard)

The plastic components meet the requirements of Directive 10/2011/EC and amendments. All materials used meet the FDA requirements according to 21 CFR.


## Technical Data

Nominal length	Filter area
30" (750 mm)	24.2 ft <sup>2</sup> (2.25 m <sup>2</sup> )

<b>Diameter:</b>	2.75 in (70 mm)
<b>Maximum operating temperature:</b>	176°F (80 °C)
<b>Maximum differential pressure in flow direction:</b>	72.5 psid at 68°F (500 kPa, 5.0 bar at 20°C) 29 psid at 176°F (200 kPa, 2.0 bar at 80°C) 4 psid at 250 °F (30 kPa, 0.3 bar at 121°C)
<b>Maximum differential pressure against flow direction:</b>	29 psid at 68°F (200 kPa, 2.0 bar at 20°C)
<b>Hot water sanitization:</b>	Max. 194°F (90°C), 30 minutes
<b>Steam sterilization:</b>	Max. 250°F (121°C) 100 cycles at 221°F (105°C) for 30 minutes

## Flow Rate

30" with water at 68°F (20°C) (standard values)



## Integrity Test

Types	Test pressure psi	Test pressure (bar)	Max. diffusion rate per 10" element
PSA02	36	(2.5)	<= 20 ml/min

The operation manual supplied with the device describes the procedure for the integrity test.

## Titer Reduction

Pore size	Test organism	Titer reduction/cm <sup>2</sup> (LRV)
PSA02 (0.20 µm)	<i>Brevundimonas diminuta</i>	>10 <sup>7</sup> (LRV >7)

## Adapter Codes

Code 2	Code 7
Single open end (SOE) 2-222 O-ring triple bayonet adapter with spear	Single open end (SOE) 2-226 O-ring double bayonet adapter with spear



## Ordering Information

---

BECO MEMBRAN PS Aqua filter cartridges with protective foil in carton.

Type	Retention rating	Adapter	Nominal length	Gasket
PSA	02 = 0.20 µm	2 = Code 2 7 = Code 7	3 = 30" (750 mm)	S = Silicone

---

## Example

---

PSA	02	7	3	S
-----	----	---	---	---

---

BECO MEMBRAN PS Aqua filter cartridges; 0.2 µm retention rating; Code 7, 30" (750 mm); silicone gasket

## Sterilization

---

### Steam Sterilization

With steam at 230°F (110°C)/7.25 psi (50 kPa, 0.5 bar).

Duration: 30 minutes after steam emerges from all openings of the filtration system.

### Hot Water Sanitization

Using water up to 194°F (90°C) max.

Duration: at least 30 minutes once the temperature reaches 185°F (85°C) from all openings of the filtration system. Soften and filter (ca. 1 µm) the water to avoid lime precipitation that could lead to premature clogging of the filter cartridge.

## Storage

---

Store cartridges in their original packaging and in a dry, odor-free and UV ray protected place.

Use filter cartridges within 60 months after production date.

## Certified Quality

---

During the production process, BECO MEMBRAN PS Aqua filter cartridges are regularly monitored to ensure consistent excellent quality control and are tested for 100% integrity as a part of the manufacturing process.

## Safety

---

When used as directed and handled correctly, there are no known unfavorable effects associated with this product. BECO MEMBRAN PS Aqua filter cartridges do not require the provision of safety-relevant information.

Storage, handling and transport does not present any environmental and health risks.

## Disposal

---

BECO MEMBRAN PS Aqua filter cartridges should be treated as industrial waste. Any local and other official regulations in relation to the filtered product must be followed.

**North America**  
44 Apple Street  
Tinton Falls, NJ 07724  
Toll Free: 800 656-3344  
(North America only)  
Tel: +1 732 212-4700

**Greater China**  
No. 7, Lane 280,  
Linhong Road  
Changning District, 200335  
Shanghai, P.R. China  
Tel: +86 21 2899-3687

**Europe/Africa/Middle East**  
Auf der Heide 2  
53947 Nettersheim, Germany  
Tel: +49 2486 809-0  
  
Friedensstraße 41  
68804 Altlußheim, Germany  
Tel: +49 6205 2094-0

**Asia-Pacific**  
100G Pasir Panjang Road  
#07-08 Interlocal Centre  
Singapore 118523  
Tel: +65 6825-1620

An den Nahewiesen 24  
55450 Langenlonsheim, Germany  
Tel: +49 6704 204-0



**For more information, please  
email us at [filtration@eaton.com](mailto:filtration@eaton.com)  
or visit [www.eaton.com/filtration](http://www.eaton.com/filtration)**

EN  
1A 4.3.5.4  
04-2023

© 2023 Eaton. All rights reserved. All trademarks and registered trademarks are the property of their respective owners. All information and recommendations appearing in this brochure concerning the use of products described herein are based on tests believed to be reliable. However, it is the user's responsibility to determine the suitability for his own use of such products. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Eaton as to the effects of such use or the results to be obtained. Eaton assumes no liability arising out of the use by others of such products. Nor is the information herein to be construed as absolutely complete, since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations.